

6. User guide information

6.1 Packaging

Plazit-Polygal TOPGAL panels and profiles are generally delivered in 20' and 40' box containers, protected on both sides by polyethylene sheets against scratching, and secured to prevent damage from movement within the container. The panel ends are sealed with masking tape to prevent dust and insects from entering into the fluting of the panels.

The maximum panel length is 5.8 meters for a 20' container and 11.8 meters for a 40' container. Shipping of panels of different lengths should be coordinated in advance with the regional sales manager. It is recommended to unload the containers by hand using a slanted roller conveyor with adjustable height.

PC products must be stored away from exposure to sunlight and according to the company's storage guidelines.

6.2 Storage

Store in dry, dark & well-ventilated area, with NO EXPOSURE to sunlight, wind, dirt or hard objects to prevent damage.

Store on a flat clean raised surface and placed on a soft material (cardboard) to prevent damage. Supported, sloped stacking is recommended. If stacked flat, stack to a maximum height of 1 meter (3 feet).

Outdoors, PC products should be covered with an opaque material (cardboard, wood, EPDM sheet etc.) that provides protection from the sun.

Outdoors, storage of PC products exposed to sun light will cause the protective polyethylene film to bake onto the sheet, and it WILL NOT BE ABLE TO BE REMOVED.

Outdoors, DO NOT store PC products under flexible PVC coverings.

6.3 Cleaning

Plazit-Polygal PC products - will give longer and better service life with simple cleaning:

- Rinse sheet with water
- Use warm soapy (mild liquid dish soap) water to clean sheets. If any dirt remains, gently wipe off with a soft cloth.
- Apply final rinse and dry with soft cloth, if possible, to prevent water spotting.

DO NOT use sponges, squeegees, brushes or sharp instruments as they may damage the UV protective coating and surface.